

## SECTION 1. Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product code : Hygienfresh DeoEssenze Ambienti Oro & Argan  
Trades code : A74-021  
Product line: Hygienfresh

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Deo essence multi-function environments. Smells, cleans and excited with just one spray  
Industrial Manufacturing[SU3], Private households (= general public = consumers)[SU21], Public domain  
(administration, education, entertainment, services, craftsmen)[SU22]

Uses advised against  
Do not use for purposes other than those listed

### 1.3. Details of the supplier of the safety data sheet

Tintolav s.r.l. - Via M. D' Antona 7 - 10028 Trofarello (TO) Tel. 011/649.68.27 Fax 011/649.67.42

Email: [info@tintolav.com](mailto:info@tintolav.com) - Sito internet: [www.tintolav.com](http://www.tintolav.com)

Email tecnico competente: [a.conedera@tintolav.com](mailto:a.conedera@tintolav.com)

National contact: Malta: Emergency Ambulance 112  
Accident & Emergency Department 2545 4030

### 1.4. Emergency telephone number

The UK National Poisons Emergency number +44 (0)870 600 6266  
London: Emergency 24 hour telephone +44 (0) 207188 0100

## SECTION 2. Hazards identification

### 2.1. Classification of the substance or mixture

2.1.1 Classification according to Regulation (EC) No 1272/2008:

Pictograms:  
GHS05, GHS07

Hazard Class and Category Code(s):  
Skin Sens. 1, Eye Dam. 1, Aquatic Chronic 3

Hazard statement Code(s):  
H317 - May cause an allergic skin reaction.  
H318 - Causes serious eye damage.  
H412 - Harmful to aquatic life with long lasting effects.

The product, if brought into contact with skin can cause skin sensitization.  
If brought into contact with eyes, the product causes serious damages to eyes, such as an opaque cornea or injury to iris.

The product is dangerous to the environment as it is harmful to aquatic life with long lasting effects

### 2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008:



Pictogram, Signal Word Code(s):  
GHS05, GHS07 - Danger

Hazard statement Code(s):  
H317 - May cause an allergic skin reaction.  
H318 - Causes serious eye damage.  
H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements:

General

P102 - Keep out of reach of children.

Prevention

P273 - Avoid release to the environment.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

Response

P302+P352 - IF ON SKIN: Wash with plenty of water and soap

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

Contains:

2-tridecoxyethanol, 1-(2,3,8,8-Tetramethyl-1,2,3,4,5,6,7,8-octahydronaphthalen-2-yl)ethanone

6,00% of the mixture consists of components whose toxicity is unknown.

The mixture contains 6,00% of the components of which is unknown toxicity to the aquatic environment.

Content of VOC ready to use condition: 6,59 %

### 2.3. Other hazards

The substance / mixture NOT contains substances PBT/vPvB according to Regulation (EC) No 1907/2006, Annex XIII

No information on other hazards

## SECTION 3. Composition/information on ingredients

### 3.1 Substances

Irrilevant

### 3.2 Mixtures

Refer to paragraph 16 for full text of hazard statements

Substance	Concentration	Classification	Index	CAS	EINECS	REACH
2-tridecoxyethanol - FEMA 0	> 5 <= 10%	Acute Tox. 4, H302; Eye Dam. 1, H318		24938-91-8		
Propan-2-ol - FEMA 2929	> 1 <= 5%	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	603-117-00-0	67-63-0	200-661-7	
1-(2,3,8,8-Tetramethyl-1,2,3,4,5,6,7,8-octahydronaphthalen-2-yl)ethanone - FEMA 0	> 1 <= 5%	Skin Irrit. 2, H315; Skin Sens. 1, H317; Aquatic Chronic 2, H411		54464-57-2	259-174-3	
ETHYL TRIMETHYLCYCLOPENTENE BUTENOL - FEMA 0	> 0,1 <= 1%	Skin Irrit. 2, H315; Aquatic Acute 1, H400; Aquatic Chronic 1, H410		28219-61-6	248-908-8	

Substance	Concentration	Classification	Index	CAS	EINECS	REACH
tetrasodium ethylenediaminetetraacetate	<= 0,1%	Acute Tox. 4, H302; Eye Dam. 1, H318	607-428-00-2	64-02-8	200-573-9	
Steareth-21	<= 0,1%	Skin Irrit. 2, H315; Eye Dam. 1, H318		9005-00-9	500-017-8	

**Fractionated global values**

Xn R22 = 6,08	Xi R41 = 6,09	T = 0,00	C R34 = 0,00
Xi R43 = 6,02	N R50/53 = 0,39	Xi R36/38 = 0,09	C R35 = 0,00
Xi R36 = 1,70	N R51/53 = 8,43	Xi R38 = 0,31	Xn R20/22 = 0,12
N R52/53 = 0,12	Xi = 0,09	Xn R65 = 0,08	T R23 = 0,01

**SECTION 4. First aid measures**
**4.1. Description of first aid measures**
**Inhalation:**

Air the area. Move immediately the contaminated patient from the area and keep him at rest in a well ventilated area. If you feel unwell seek medical advice.

**Direct contact with skin (of the pure product):**

In case of contact with skin, wash immediately with water and soap

**Direct contact with eyes (of the pure product):**

Wash immediately and thoroughly with running water, keeping eyelids open for at least 10 minutes, then protect your eyes with a dry sterile gauze. Seek medical advice immediately

Do not use eye drops or ointments of any kind before the examination or advice from an oculist.

**Ingestion:**

Not hazardous. It's possible to give activated charcoal in water or liquid paraffin medicine

**4.2. Most important symptoms and effects, both acute and delayed**

No data available.

**4.3. Indication of any immediate medical attention and special treatment needed**

If skin irritation or rash occurs: Get medical advice/attention.

If medical advice is needed, have product container or label at hand.

**SECTION 5. Firefighting measures**
**5.1. Extinguishing media**
**Advised extinguishing agents:**

Water spray, CO2, foam, dry chemical, depending on the materials involved in the fire.

**Extinguishing means to avoid:**

Water jets. Use water jets only to cool the surfaces of the containers exposed to fire.

**5.2. Special hazards arising from the substance or mixture**

No data available.

### **5.3. Advice for firefighters**

Use protection for the breathing apparatus

Safety helmet and full protective suit.

The spray water can be used to protect the people involved in the extinction

You may also use selfrespirator, especially when working in confined and poorly ventilated area and if you use halogenated extinguishers (Halon 1211 fluobrene, Solkan 123, NAF, etc...)

Keep containers cool with water spray

## **SECTION 6. Accidental release measures**

### **6.1. Personal precautions, protective equipment and emergency procedures**

6.1.1 For non-emergency personnel:

Leave the area surrounding the spill or release. Do not smoke

Wear mask, gloves and protective clothing.

6.1.2 For emergency responders:

Wear mask, gloves and protective clothing.

Eliminate all unguarded flames and possible sources of ignition. No smoking.

Provision of sufficient ventilation.

Evacuate the danger area and, in case, consult an expert.

### **6.2. Environmental precautions**

Contain spill with earth or sand.

If the product has entered a watercourse in sewers or has contaminated soil or vegetation, notify it to the authorities.

Discharge the remains in compliance with the regulations

### **6.3. Methods and material for containment and cleaning up**

6.3.1 For containment:

Rapidly recover the product, wear a mask and protective clothing

Recover the product for reuse, if possible, or for removal. Possibly absorb it with inert material.

Prevent it from entering the sewer system.

6.3.2 For cleaning up:

After wiping up, wash with water the area and materials involved

6.3.3 Other information:

None in particular.

### **6.4. Reference to other sections**

Refer to paragraphs 8 and 13 for more information

## **SECTION 7. Handling and storage**

### **7.1. Precautions for safe handling**

Avoid contact and inhalation of vapors

At work do not eat or drink.

See also paragraph 8 below.

### **7.2. Conditions for safe storage, including any incompatibilities**

Keep in original container closed tightly. Do not store in open or unlabeled containers.

Keep containers upright and safe by avoiding the possibility of falls or collisions.

Store in a cool place, away from sources of heat and direct exposure of sunlight.

### 7.3. Specific end use(s)

Industrial Manufacturing:

Handle with extreme caution.

Store in a well ventilated place away from heat sources.

Private households (= general public = consumers):

Handle with care.

Store in ventilated place away from heat sources,

Keep the container tightly closed.

Public domain (administration, education, entertainment, services, craftsmen):

Handle with care. Store in a ventilated area and away from heat, keep the container tightly closed.

## SECTION 8. Exposure controls/personal protection

### 8.1. Control parameters

Related to contained substances:

Propan-2-ol:

TLV: TWA 200 ppm 400 ppm as STEL A4 (not classifiable as a human carcinogen); (ACGIH 2004).

MAK: 200 ppm 500 mg/m peak limitation Category: II (2); Risk group for pregnancy: C; (DFG 2004).

### 8.2. Exposure controls



Appropriate engineering controls:

Industrial Manufacturing:

No specific monitoring foreseen

Private households (= general public = consumers):

No specific checks planned

Public domain (administration, education, entertainment, services, craftsmen):

No specific monitoring foreseen

Individual protection measures:

(a) Eye / face protection

When handling the pure product use safety glasses (spectacles cage) (EN 166).

(b) Skin protection

(i) Hand protection

When handling the pure product use chemical resistant protective gloves (EN 374-1/EN374-2/EN374-3)

(ii) Other

When handling the pure product wear full protective skin clothing.

(c) Respiratory protection

Not needed for normal use.

(d) Thermal hazards

No hazard to report

Environmental exposure controls:

Use according to good working practices to avoid pollution into the environment.

**SECTION 9. Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical and chemical properties	Value	Determination method
Appearance	Milky liquid	
Odour	characteristic	
Odour threshold	not determined	
pH	7	
Melting point/freezing point	not determined	
Initial boiling point and boiling range	not determined	
Flash point	> 60 °C	ASTM D92
Evaporation rate	irrelevant	
Flammability (solid, gas)	nonflammable	
Upper/lower flammability or explosive limits	not determined	
Vapour pressure	not determined	
Vapour density	not determined	
Relative density	1	
Solubility	soluble in water	
Water solubility	completely soluble in water	
Partition coefficient: n-octanol/water	not determined	
Auto-ignition temperature	not determined	
Decomposition temperature	not determined	
Viscosity	not determined	
Explosive properties	not explosive	
Oxidising properties	non-oxidizing	

**9.2. Other information**

Content of VOC ready to use condition: 6,59 %

**SECTION 10. Stability and reactivity****10.1. Reactivity**

No reactivity hazards

**10.2. Chemical stability**

No hazardous reaction when handled and stored according to provisions.

**10.3. Possibility of hazardous reactions**

There are no hazardous reactions

#### 10.4. Conditions to avoid

Nothing to report

#### 10.5. Incompatible materials

It can generate inflammable gases to contact with elementary metals, nitrides, inorganic sulfide, strong reducing agents.

It can generate toxic gases to contact with inorganic sulfide, strong reducing agents.

#### 10.6. Hazardous decomposition products

Does not decompose when used for intended uses.

### SECTION 11. Toxicological information

#### 11.1. Information on toxicological effects

ATE(mix) oral = 8.333,3 mg/kg

ATE(mix) dermal = 0,0 mg/kg

ATE(mix) inhal = 0,0 mg/l/4 h

(a) acute toxicity: 1-(2,3,8,8-Tetramethyl-1,2,3,4,5,6,7,8-octahydronaphthalen-2-yl)ethanone: TOXIC DOSE 1-LD > 50 5000 mg/kg (oral rat)

TOXIC DOSE 2-LD > 50 5000 mg/kg (skn-rbt)

(b) skin corrosion/irritation Propan-2-ol: Skin-rabbit

Result: Mild skin irritation

(c) serious eye damage/irritation: If brought into contact with eyes, the product causes serious damages to eyes, such as an opaque cornea or injury to iris.

Propan-2-ol: Eyes-rabbit

Result: Eye irritation- 24 h

(d) respiratory or skin sensitization: The product, if brought into contact with skin can cause skin sensitization.

(e) germ cell mutagenicity: not applicable

(f) carcinogenicity: not applicable

(g) reproductive toxicity: not applicable

(h) specific target organ toxicity (STOT) single exposure: not applicable

(i) specific target organ toxicity (STOT) repeated exposure not applicable

(j) aspiration hazard: not applicable

Related to contained substances:

Propan-2-ol:

ROUTES of EXPOSURE: the substance can be absorbed into the body by inhalation of its fumes.

INHALATION RISK: A harmful contamination of the air will be reached quite slowly due to evaporation of the substance at 20 C; However, for spraying or scattering, much more quickly.

Effects of short-term exposure: the substance is irritating to the eyes and the respiratory tract the substance may cause effects on the central nervous system, causing depression. Much greater exposure to the OEL may lead to unconsciousness.

Effects of REPEATED EXPOSURE or long term: the liquid degreasing the skin features.

ACUTE HAZARDS/Symptoms INHALATION Cough. Vertigo. Drowsiness. Headaches. Sore throat. See If Swallowed. CUTE CUTE.

EYE Redness.

INGESTION abdominal pain. Difficulty in breathing. Nausea. State of unconsciousness. Vomiting. (Further see inhalation).

NOT and use of alcoholic beverages enhances the harmful effect.

LD50 (rat) Oral (mg/kg body weight) = 2100

LD50 Dermal (rat or rabbit) (mg/kg body weight) = 2100

CL50 Inhalation (rat) vapour/dust/mist/fume (mg/l/4h) or gas (ppmV/4h) = 29

1-(2,3,8,8-Tetramethyl-1,2,3,4,5,6,7,8-octahydronaphthalen-2-yl)ethanone:

LD50 (rat) Oral (mg/kg body weight) = 5000

LD50 Dermal (rat or rabbit) (mg/kg body weight) = 5000

ETHYL TRIMETHYLCYCLOPENTENE BUTENOL:

LD50 (rat) Oral (mg/kg body weight) = 5000

LD50 Dermal (rat or rabbit) (mg/kg body weight) = 2000

tetrasodium ethylenediaminetetraacetate:

Routes of Entry: Absorbed through skin. Eye contact. Inhalation. Ingestion.

Toxicity to Animals: Acute oral toxicity (LD50): >2000 mg/kg [Rat].

Chronic Effects on Humans: May cause damage to the following organs: upper respiratory tract, skin, eyes.

Other Toxic Effects on Humans: Slightly hazardous in case of skin contact (irritant), of ingestion, of inhalation.

Special Remarks on Toxicity to Animals: Not available.

Special Remarks on Chronic Effects on Humans: Not available.

Special Remarks on other Toxic Effects on Humans: Acute Potential Health effects: Skin: May cause skin irritation.

Eyes:

May cause eye irritation. Inhalation: May cause irritation of the respiratory tract. Ingestion: May cause gastrointestinal tract

irritation. The toxicological properties of this substance have not been fully investigated.

LD50 (rat) Oral (mg/kg body weight) = 2000

Steareth-21:

LD50 (rat) Oral (mg/kg body weight) = 15000

## SECTION 12. Ecological information

### 12.1. Toxicity

Related to contained substances:

2-tridecoxyethanol:

Acute toxicity to fish

LC50 - 96 h : 7.5 mg/l - *Lepomis macrochirus* (Bluegill sunfish)

Harmful to fish.

LC50 - 96 h : 12 mg/l - *Danio rerio* (zebra fish)

Method: OECD Test Guideline 203

Harmful to fish.

Acute toxicity to daphnia and other aquatic invertebrates.

Tridecyl alcohol ethoxylated : LC50 - 48 h : 4.7 mg/l - *Daphnia magna* (Water flea)

Method: OECD Test Guideline 202

Toxic to aquatic invertebrates.

Toxicity to aquatic plants

Tridecyl alcohol ethoxylated : ErC50 - 72 h : 17 mg/l - *Scenedesmus subspicatus*

Harmful to algae.

C(E)L50 (mg/l) = 4,7

Propan-2-ol:

Toxicity to fish LC50-*Pimephales promelas* (fathead minnow)-9, 640.00 mg/l-96 h

Toxicity to daphnia and other aquatic invertebrates

-EC50 *Daphnia magna* (Water flea)-5, 102.00 mg/l- 24 h

EC50 Immobilization-*Daphnia magna* (Water flea)-6.851 mg/l- 24h

C(E)L50 (mg/l) = 5102

1-(2,3,8,8-Tetramethyl-1,2,3,4,5,6,7,8-octahydronaphthalen-2-yl)ethanone:

Endpoint: LC50 species: lepomis macrochirus (fish-salt Bluegrill) = 1.30 mg/l-h Duration: 96-Note:: method: OECD 203 TG

Endpoint: EC50-species: Daphnia magna (Water flea) = 1.38 mg/l-h Duration: 48-comments:: semi-static test method: OECD TG 202

Endpoint: EC50 Desmodesmus subspicatus-species (green algae) = 2.60 mg/l-h Duration: 72-

Note:: static test method: OECD TG201

C(E)L50 (mg/l) = 1,3

tetrasodium ethylenediaminetetraacetate:

Ecotoxicity: Ecotoxicity in water (LC50): 760 mg/l 96 hours [Bull gill sunfish]. 59.8 mg/l 96 hours [Fathead Minnow].

BOD5 and COD: Not available.

Products of Biodegradation: Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.

Toxicity of the Products of Biodegradation: The product itself and its products of degradation are not toxic.

Special Remarks on the Products of Biodegradation: Not available.

C(E)L50 (mg/l) = 500

Stearth-21:

LC50/83d > Oncochinchus mykiss-5.6 mg/l

C(E)L50 (mg/l) = 5,6

The product is dangerous for the environment as it is toxic for aquatic organisms following acute exposure.

Use according to good working practices to avoid pollution into the environment.

### **12.2. Persistence and degradability**

Related to contained substances:

2-tridecoxyethanol:

The substance fulfills the criteria for ultimate aerobic biodegradability and ready biodegradability

tetrasodium ethylenediaminetetraacetate:

Partly biodegradable according to OECD test

-BOD5: 50 mg O2/g

-COD: 260 mg O2/g

### **12.3. Bioaccumulative potential**

Related to contained substances:

tetrasodium ethylenediaminetetraacetate:

None of the components bio-accumulative

### **12.4. Mobility in soil**

No data available.

### **12.5. Results of PBT and vPvB assessment**

The substance / mixture NOT contains substances PBT/vPvB according to Regulation (EC) No 1907/2006, Annex XIII

---

#### **12.6. Other adverse effects**

No adverse effects

### **SECTION 13. Disposal considerations**

#### **13.1. Waste treatment methods**

Do not reuse empty containers. Dispose of them in accordance with the regulations in force. Any remaining product should be disposed of according to applicable regulations by addressing to authorized companies.

Recover if possible. Operate according to local or national regulations

### **SECTION 14. Transport information**

#### **14.1. UN number**

3082

ADR exemption because compliance with the following characteristics:

Combination packagings: per inner packaging 5 L per package 30 Kg

Inner packagings placed in skrink-wrapped or stretch-wrapped trays: per inner packaging 5 L per package 20 Kg



#### **14.2. UN proper shipping name**

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (thylenediaminetetraacetate, Propan-2-ol, 1-(2,3,8,8-Tetramethyl-1,2,3,4,5,6,7,8-octahydronaphthalen-2-yl)ethanone, ETHYL TRIMETHYLCYCLOPENTENE BUTENOL)

#### **14.3. Transport hazard class(es)**

Class : 9

Label : 9

Tunnel restriction code : E

Limited quantities : 5 L

EmS : F-A, S-F

#### **14.4. Packing group**

III

#### **14.5. Environmental hazards**

Product is environmentally hazardous

Marine polluting agent : Not

#### **14.6. Special precautions for user**

No data available.

#### **14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

It is not intended to carry bulk

### **SECTION 15. Regulatory information**

---

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

No data available.

**15.2. Chemical safety assessment**

The supplier has made an assessment of chemical safety

**SECTION 16. Other information**

**16.1. Other information**

Description of the hazard statements exposed to point 3

H302 = Harmful if swallowed.

H318 = Causes serious eye damage.

H225 = Highly flammable liquid and vapour.

H319 = Causes serious eye irritation.

H336 = May cause drowsiness or dizziness.

H315 = Causes skin irritation.

H317 = May cause an allergic skin reaction.

H411 = Toxic to aquatic life with long lasting effects.

H400 = Very toxic to aquatic life.

H410 = Very toxic to aquatic life with long lasting effects.

Classification based on data of all mixture components

Main normative references:

Directive 1999/45/EC

Directive 2001/60/EC

Regulation 1272/2008/EC

Regulation 2010/453/EC

\*\* The information contained herein is based on our knowledge at the date above.

Related solely to the product and do not constitute a guarantee of a particular quality.

It is the duty of the user to ensure that these are appropriate and complete information regarding the specific use intended.

This data sheet cancels and replaces any previous edition.

---