

SECTION 1. Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Product code : Hygienfresh Pavimenti/Superfici Passion Fruit
Trades code : A85-010
Product line: Hygienfresh

1.2. Relevant identified uses of the substance or mixture and uses advised against

Deo Super clean floors with long-lasting scent

Sectors of use:

Industrial Manufacturing[SU3], Private households (= general public = consumers)[SU21], Public domain (administration, education, entertainment, services, craftsmen)[SU22]

Uses advised against

Do not use for purposes other than those listed

1.3. Details of the supplier of the safety data sheet

Tintolav s.r.l. - Via M. D' Antona 7 - 10028 Trofarello (TO) Tel. 011/649.68.27 Fax 011/649.67.42

Email: info@tintolav.com - Sito internet: www.tintolav.com

Email tecnico competente: a.conedera@tintolav.com

National contact: Malta: Emergency Ambulance 112
Accident & Emergency Department 2545 4030

1.4. Emergency telephone number

The UK National Poisons Emergency number +44 (0)870 600 6266
London: Emergency 24 hour telephone +44 (0) 207188 0100

SECTION 2. Hazards identification**2.1. Classification of the substance or mixture**

2.1.1 Classification according to Regulation (EC) No 1272/2008:

Pictograms:
GHS07

Hazard Class and Category Code(s):
Eye Irrit. 2

Hazard statement Code(s):
H319 - Causes serious eye irritation.

If brought into contact with eyes, the product, causes significant irritations which may last for more than 24 hours.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008:

Pictogram, Signal Word Code(s):
GHS07 - Warning

Hazard statement Code(s):



H319 - Causes serious eye irritation.

Supplemental Hazard statement Code(s):

EUH208 - Contains 2-Methylundecanal, 4-tert-Butylcyclohexyl acetate, reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.

Precautionary statements:

General

P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

Prevention

P264 - Wash your hand thoroughly after handling.

Response

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 - If eye irritation persists: Get medical advice/attention.

Contains:

Fatty alcohol ethoxylate, tetrasodium ethylenediaminetetraacetate, Propan-2-ol, ethanol, Steareth-21, Sodium dodecylbenzenesulfonate, Allyl hexanoate, 3-(o-Ethylphenyl)-2,2-dimethylpropionaldehyde, alpha-Methyl-1,3-benzodioxole-5-propionaldehyde, alpha-Hexylcinnamaldehyde, 3a,4,5,6,7,7a-hexahydro-4,7-methano-1H-inden-6-yl propionate, Diethyl malonate, ethyl 2,3-epoxy-3-phenylbutyrate, Eugenol, 2,4-dimethylcyclohex-3-ene-1-carbaldehyde, Isoeugenol, dipentene, 2-(4-tert-butylbenzyl)propionaldehyde, 4-tert-Butylcyclohexyl acetate
0,05% of the mixture consists of components whose toxicity is unknown.

Contains (Reg.EC 648/2004):

< 5% perfumes, Miscela di: 5-cloro-2-metil-2H-isotiazol-3-one [EC no. 247-500-7]; 2-metil-2H-isotiazol-3-one [EC no. 220-239-6], Dye, anionic surfactants, non-ionic surfactants, alpha-Hexylcinnamaldehyde, D-Limonene ((S)-p-menta-1,8-diene), BUTYLPHENYL METHYLPROPIONAL

Content of VOC ready to use condition: 5,21 %

2.3. Other hazards

The substance / mixture NOT contains substances PBT/vPvB according to Regulation (EC) No 1907/2006, Annex XIII

No information on other hazards

SECTION 3. Composition/information on ingredients

3.1 Substances

Irrilevant

3.2 Mixtures

Refer to paragraph 16 for full text of hazard statements

Substance	Concentration	Classification	Index	CAS	EINECS	REACH
Propan-2-ol - FEMA 2929	> 1 <= 5%	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	603-117-00-0	67-63-0	200-661-7	
Fatty alcohol ethoxylate	> 1 <= 5%	Acute Tox. 4, H302; Eye Dam. 1, H318		64425-86-1		02-2119548 515-35-000 0

Substance	Concentration	Classification	Index	CAS	EINECS	REACH
Sodium Lauryl Ether sulfate	> 1 <= 5%	Skin Irrit. 2, H315; Eye Dam. 1, H318; Aquatic Chronic 3, H412		68891-38-3	500-234-8	01-2119488 639-16
ethanol	> 0,1 <= 1%	Flam. Liq. 2, H225	603-002-00-5	64-17-5	200-578-6	
4-tert-Butylcyclohexyl acetate - FEMA 0	> 0,1 < 1%	Skin Sens. 1B, H317; Aquatic Chronic 2, H411		32210-23-4	250-954-9	

SECTION 4. First aid measures

4.1. Description of first aid measures

Inhalation:

Air the area. Move immediately the contaminated patient from the area and keep him at rest in a well ventilated area. If you feel unwell seek medical advice.

Direct contact with skin (of the pure product):

Take contaminated clothing Immediately off.

Wash immediately with plenty of running water and possibly with soap, the areas of the body that have, or are only suspected to have, come in contact with the product.

In case of contact with skin, wash immediately with water and soap.

Direct contact with eyes (of the pure product):

Wash immediately and thoroughly with running water, keeping eyelids open for at least 10 minutes, then protect your eyes with a dry sterile gauze. Seek medical advice immediately

Ingestion:

Not hazardous. It's possible to give activated charcoal in water or liquid paraffin medicine

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

If eye irritation persists: Get medical advice/attention.

If medical advice is needed, have product container or label at hand.

SECTION 5. Firefighting measures

5.1. Extinguishing media

Advised extinguishing agents:

Water spray, CO2, foam, dry chemical, depending on the materials involved in the fire.

Extinguishing means to avoid:

Water jets. Use water jets only to cool the surfaces of the containers exposed to fire.

5.2. Special hazards arising from the substance or mixture

No data available.

5.3. Advice for firefighters

Use protection for the breathing apparatus
Safety helmet and full protective suit.
The spray water can be used to protect the people involved in the extinction
You may also use selfrespirator, especially when working in confined and poorly ventilated area and if you use
halogenated extinguishers (Halon 1211 fluobrene, Solkan 123, NAF, etc...)
Keep containers cool with water spray

SECTION 6. Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****6.1.1 For non-emergency personnel:**

Leave the area surrounding the spill or release. Do not smoke
Leave the surrounding area recalling that any overheating could project the cylinder at a considerable distance.
Wear mask, gloves and protective clothing.

6.1.2 For emergency responders:

Given the tightness of aerosol, it is unlikely that the spillage may occur.
However if some container is damaged likely to cause a loss, insulate the tank in question by bringing it to open air or covering it with inert material and fuel (eg sand, earth, vermiculite) and having the care to avoid any point of ignition that might pose a serious risk of fire.
Wear mask, gloves and protective clothing.
Eliminate all unguarded flames and possible sources of ignition. No smoking.
Provision of sufficient ventilation.
Evacuate the danger area and, in case, consult an expert.

6.2. Environmental precautions

Contain spill with earth or sand.
If the product has entered a watercourse in sewers or has contaminated soil or vegetation, notify it to the authorities.
Discharge the remains in compliance with the regulations

6.3. Methods and material for containment and cleaning up**6.3.1 For containment:**

Rapidly recover the product, wear a mask and protective clothing
Recover the product for reuse, if possible, or for removal. Possibly absorb it with inert material.
Prevent it from entering the sewer system.

6.3.2 For cleaning up:

After wiping up, wash with water the area and materials involved

6.3.3 Other information:

None in particular.

6.4. Reference to other sections

Refer to paragraphs 8 and 13 for more information

SECTION 7. Handling and storage**7.1. Precautions for safe handling**

Avoid contact and inhalation of vapors
At work do not eat or drink.
Wear protective gloves/protective clothing/eye protection/face protection.

See also paragraph 8 below.

7.2. Conditions for safe storage, including any incompatibilities

Keep in original container closed tightly. Do not store in open or unlabeled containers.
Keep containers upright and safe by avoiding the possibility of falls or collisions.
Store in a cool place, away from sources of heat and direct exposure of sunlight.

7.3. Specific end use(s)

Industrial Manufacturing:
Handle with extreme caution.
Store in a well ventilated place away from heat sources.

Private households (= general public = consumers):
Handle with care.
Store in ventilated place away from heat sources,
Keep the container tightly closed.

Public domain (administration, education, entertainment, services, craftsmen):
Handle with care. Store in a ventilated area and away from heat, keep the container tightly closed.

SECTION 8. Exposure controls/personal protection**8.1. Control parameters**

Related to contained substances:

Propan-2-ol:

TLV: TWA 200 ppm 400 ppm as STEL A4 (not classifiable as a human carcinogen); (ACGIH 2004).

MAK: 200 ppm 500 mg/m peak limitation Category: II (2); Risk group for pregnancy: C; (DFG 2004).

ethanol:

Component CAS-No. Value Control parameters

Basis

Ethanol-17-64 TWA 5 ppm 1.000

1.920 mg/m³

UK. EH40 WEL-Workplace Exposure Limits

Remarks Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used

- Substance: Propan-2-ol

DNEL

Systemic effects Long term Workers inhalation = 500 (mg/m³)

Systemic effects Long term Workers dermal = 880 (mg/kg bw/day)

Systemic effects Long term Consumers inhalation = 319 (mg/m³)

Systemic effects Long term Consumers dermal = 26 (mg/kg bw/day)

PNEC

Sweet water = 140,9 (mg/l)

sediment Sweet water = 552 (mg/kg/sediment)

Sea water = 140,9 (mg/l)

sediment Sea water = 552 (mg/kg/sediment)

ground = 28 (mg/kg ground)

- Substance: ethanol

DNEL

Systemic effects Long term Workers inhalation = 950 (mg/m³)

8.2. Exposure controls

Appropriate engineering controls:
Industrial Manufacturing:
No specific monitoring foreseen

Private households (= general public = consumers):
No specific checks planned

Public domain (administration, education, entertainment, services, craftsmen):
No specific monitoring foreseen

Individual protection measures:

(a) Eye / face protection
Not needed for normal use.

(b) Skin protection

(i) Hand protection
Manipulate with gloves. The gloves should be checked before being used. Use a technique suitable for the removal of gloves (without touching the outside of the glove) to avoid skin contact with this product dispose of contaminated gloves after use in accordance with the legislation and good laboratory practices. Wash and dry your hands.
Selected protective gloves shall comply with the requirements of EU Directive 89/686/EEC and EN 374 standards arising therefrom.

Full contact

Material: nitrile rubber
minimum thickness: 0.11 mm
permeation time: 480 min

(ii) Other
Wear normal work clothing.

(c) Respiratory protection
Not needed for normal use.

(d) Thermal hazards
No hazard to report

Environmental exposure controls:

Use according to good working practices to avoid pollution into the environment.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical and chemical properties	Value	Determination method
Appearance	Red Liquid	
Odour	characteristic	
Odour threshold	not determined	
pH	7	

Physical and chemical properties	Value	Determination method
Melting point/freezing point	not determined	
Initial boiling point and boiling range	not determined	
Flash point	> 60 °C	ASTM D92
Evaporation rate	irrelevant	
Flammability (solid, gas)	nonflammable	
Upper/lower flammability or explosive limits	not determined	
Vapour pressure	not determined	
Vapour density	not determined	
Relative density	1	
Solubility	soluble in water	
Water solubility	completely soluble in water	
Partition coefficient: n-octanol/water	not determined	
Auto-ignition temperature	not determined	
Decomposition temperature	not determined	
Viscosity	not determined	
Explosive properties	not explosive	
Oxidising properties	non-oxidizing	

9.2. Other information

Content of VOC ready to use condition: 5,21 %

SECTION 10. Stability and reactivity

10.1. Reactivity

No reactivity hazards

10.2. Chemical stability

No hazardous reaction when handled and stored according to provisions.

10.3. Possibility of hazardous reactions

There are no hazardous reactions

10.4. Conditions to avoid

Nothing to report

10.5. Incompatible materials

It can generate inflammable gases to contact with elementary metals, nitrides, inorganic sulfide, strong reducing agents.

It can generate toxic gases to contact with inorganic sulfide, strong reducing agents.

10.6. Hazardous decomposition products

Does not decompose when used for intended uses.

SECTION 11. Toxicological information**11.1. Information on toxicological effects**

ATE(mix) oral = 45.150,9 mg/kg

ATE(mix) dermal = 222.222,2 mg/kg

ATE(mix) inhal = ∞

(a) acute toxicity: ethanol: LD50 Oral-rat-7.060 mg/kg

Remarks: Lungs, Thorax, or Respiration: Other changes.

LC50 Inhalation-rat-10:0-20000 ppm

4-tert-Butylcyclohexyl acetate: Rats (10 per dose, sex and strain not reported) were administered 4-tert-butylcyclohexyl acetate by gavage at 5000 mg/kg-bw. No information on mortality was reported. Rabbits (4, sex and strain not reported) were administered 4-tert-butylcyclohexyl acetate dermally at 5000 mg/kg-bw. One rabbit died.

(b) skin corrosion/irritation Propan-2-ol: Skin-rabbit

Result: Mild skin irritation

Sodium Lauryl Ether sulfate: Acute effects: contact with eyes will cause irritation; symptoms may include: redness, edema, pain and tears.

Through contact with the skin has irritation with erythema, edema, dryness and cracking.

ethanol: Skin-rabbit

Result: Irritating to skin. -12:0 am

4-tert-Butylcyclohexyl acetate: Rabbits (species, sex and number not specified) were administered 4-tert-butylcyclohexyl acetate dermally to the ears and backs. Observations of the backs included slight erythema after 1 and 5 min, severe erythema and slight edema at 15 min, and severe erythema and edema at 20 hours. On day 8, slight redness and severe scaling were observed. Observations of the ears included severe erythema and edema with blistering after 20 hours. Severe necrosis was recorded on day 8. (Bhatia, S.P., et al., Food and Chemical Toxicology 46 (2008) S36-S41) 4-tert-Butylcyclohexyl acetate was irritating to rabbit skin

(c) serious eye damage/irritation: If brought into contact with eyes, the product, causes significant irritations which may last for more than 24 hours.

ethanol: Eyes-rabbit

Result: Mild eye irritation-12:0 am

(Draize Test)

Propan-2-ol: Eyes-rabbit

Result: Eye irritation- 24 h

4-tert-Butylcyclohexyl acetate: Albino rabbits (3/sex dose not specified) were instilled 0.1 mL aliquot of 0.625% solution (vehicle not reported) into the right eye of each rabbit with no further treatment while the left eye served as control. Scores were recorded according to the Draize scale. Slight to moderate irritation with conjunctival chemosis and discharge were observed in all three rabbits (mean score for redness and 1.9 for 1 chemosis). All eyes cleared by day 4. (Bhatia, S.P., et al., Food and Chemical Toxicology 46 (2008) S36-S41) 4-tert-Butylcyclohexyl acetate was irritating to rabbit eyes.

(d) respiratory or skin sensitization: based on available data, the classification criteria are not met.

(e) germ cell mutagenicity: 4-tert-Butylcyclohexyl acetate: Salmonella typhimurium strains TA98, TA100, TA1535, TA1537 and Ta 1538 were exposed to 4-tert-butylcyclohexyl acetate at 8 to 5000 g/plate in a bacterial reverse mutation assay in the presence and absence of metabolic activation. Positive and negative controls were used but their response was not provided. Cytotoxicity was observed at and above 200 g/plate.

4-tert-Butylcyclohexyl acetate was not mutagenic in this assay.

(f) carcinogenicity: based on available data, the classification criteria are not met.

(g) reproductive toxicity: ethanol: Reproductive toxicity-Human-female-Oral

Effects on Newborn: Apgar score (human only). Effects on Newborn: Other measures or neonatal effects.

Effects on Newborn: Drug dependence.

(h) specific target organ toxicity (STOT) single exposure: based on available data, the classification criteria are not met.

(i) specific target organ toxicity (STOT) repeated exposure 4-tert-Butylcyclohexyl acetate: In a modified developmental toxicity screening test (OCED TG 421), CrI: CD pregnant (SD) rats were administered 4-tert-butylcyclohexyl acetate (a

mixture of 71% 28% trans and cis) in corn oil by gavage at 0, 40, 160 or 640 mg/kg-bw per day during gestation days 7-20. Rats were Caesarean-sectioned on day 21 of gestation and examined for number and distribution of corpora lutea, implantation sites and placenta. Live and dead fetuses and early and late resorptions were recorded. Fetuses were examined for sex ratio, gross external alterations and skeletal and soft tissue alterations. There were no effects on maternal body weights, weight gain, food consumption or organ weights. Pup viability, body weights, external observations and microscopic examination showed no significant alterations that could be related to the administration of the test substance.

NOAEL (maternal or developmental toxicity) = 640 mg/kg-bw/day (based on no effects at the highest dose tested)

(j) aspiration hazard: based on available data, the classification criteria are not met.

Related to contained substances:

Propan-2-ol:

ROUTES of EXPOSURE: the substance can be absorbed into the body by inhalation of its fumes.

INHALATION RISK: A harmful contamination of the air will be reached quite slowly due to evaporation of the substance at 20 °C; However, for spraying or scattering, much more quickly.

Effects of short-term exposure: the substance is irritating to the eyes and the respiratory tract the substance may cause effects on the central nervous system, causing depression. Much greater exposure to the OEL may lead to unconsciousness.

Effects of REPEATED EXPOSURE or long term: the liquid degreasing the skin features.

ACUTE HAZARDS/Symptoms INHALATION Cough. Vertigo. Drowsiness. Headaches. Sore throat. See If Swallowed. CUTE CUTE.

EYE Redness.

INGESTION abdominal pain. Difficulty in breathing. Nausea. State of unconsciousness. Vomiting. (Further see inhalation).

NOT and use of alcoholic beverages enhances the harmful effect.

LD50 (rat) Oral (mg/kg body weight) = 2100

LD50 Dermal (rat or rabbit) (mg/kg body weight) = 2100

CL50 Inhalation (rat) vapour/dust/mist/fume (mg/l/4h) or gas (ppmV/4h) = 29

Fatty alcohol ethoxylate:

LD50 (rat) Oral (mg/kg body weight) = 3100

Sodium Lauryl Ether sulfate:

LD50 (alcohols, C12-14, ethoxylated, sulfated, sodium salts; CAS No.: 68891-38-3)

Via Inhalation Administration:

Test species: rat

Value: 4100 mg/kg

Specification: LD50 (alcohols, C12-14, ethoxylated, sulfated, sodium salts; CAS No.: 68891-38-3)

Via Dermal intake:

Test species: rat

Value: > 2000 mg/kg

LD50 (rat) Oral (mg/kg body weight) = 2000

LD50 Dermal (rat or rabbit) (mg/kg body weight) = 2000

CL50 Inhalation (rat) vapour/dust/mist/fume (mg/l/4h) or gas (ppmV/4h) = 4100

ethanol:

ROUTES of EXPOSURE: the substance can be absorbed into the body by inhalation of its fumes and ingestion.

INHALATION RISK: A harmful contamination of the air will be reached quite slowly due to evaporation of the substance at 20 °C.

Effects of short-term exposure: the substance is irritating to the eyes. Inhalation of high vapour can cause irritation of the eyes and respiratory tract. The substance may cause effects on the central nervous system effects of

REPEATED EXPOSURE or long term: the liquid degreasing the skin features. The substance may have an effect on the high central nervous system respiratory tract, causing irritation, headaches, fatigue and lack of concentration. See Notes.

ACUTE HAZARDS/Symptoms INHALATION Cough. Headaches. Fatigue. Drowsiness.

CUTE CUTE.

EYE Redness. Pain. Burning.

SWALLOWED burning sensation. Headaches. Confusion. Vertigo. State of unconsciousness.

N O T and consumption of ethanol during pregnancy can have adverse effects on the unborn child. Chronic ethanol ingestion can cause cirrhosis of the liver.

LD50 (rat) Oral (mg/kg body weight) = 7060

LD50 Dermal (rat or rabbit) (mg/kg body weight) = 20000

CL50 Inhalation (rat) vapour/dust/mist/fume (mg/l/4h) or gas (ppmV/4h) = 20000

4-tert-Butylcyclohexyl acetate:

LD50 (rat) Oral (mg/kg body weight) = 5000

LD50 Dermal (rat or rabbit) (mg/kg body weight) = 5000

SECTION 12. Ecological information

12.1. Toxicity

Related to contained substances:

Propan-2-ol:

Toxicity to fish LC50-Pimephales promelas (fathead minnow)-9, 640.00 mg/l-96 h

Toxicity to daphnia and other aquatic invertebrates

-EC50 Daphnia magna (Water flea)-5, 102.00 mg/l- 24 h

EC50 Immobilization-Daphnia magna (Water flea)-6.851 mg/l- 24h

C(E)L50 (mg/l) = 5102

Fatty alcohol ethoxylate:

Ittiotossicit:

LC50 (96 h) 1-10 mg/l, Brachydanio rerio

Aquatic invertebrates:

EC50 (48 h) 1-10 mg/l Daphnia magna

Aquatic plants:

EC50 (72 h) 1-10 mg/l Scenedesmus subspicatus

Microorganisms/effects on activated sludge:

CE10 > 1,000 mg/l, activated sludge (DEV-L2)

Chronic toxic to aquatic invertebrates:

NOEC (21 d), 0.33 mg/l Daphnia magna

C(E)L50 (mg/l) = 1

Sodium Lauryl Ether sulfate:

LC50 (alcohols, C12-14, ethoxylated, sulfated, sodium salts; CAS No.: 68891-38-3)

Parametro: Fish

Danio Rerio

Value = 7.1 mg/l

For. test: 96 h

Specification: EC50 (alcohols, C12-14, ethoxylated, sulfated, sodium salts; CAS No.: 68891-38-3)

Parametro: Daphnia

Daphnia magna

Value = 7.2 mg/l

For. test: 48 h

Specification: EC50 (alcohols, C12-14, ethoxylated, sulfated, sodium salts; CAS No.: 68891-38-3)

Parametro: Algae

Scenedesmus subspicatus

Value = 27 mg/l

C(E)L50 (mg/l) = 7,1

ethanol:

C(E)L50 (mg/l) = 11200

4-tert-Butylcyclohexyl acetate:

Golden ide (*Leuciscus idus*) were exposed to 4-tert-butylcyclohexyl acetate at nominal concentrations of 0, 10, 13, 16 and 20 mg/L under static conditions for 48 hours. EF Marlowet was used as a solubilizer. Mortality was 0, 10, 100 and 80% at 10, 13, 16 and 20 mg/L.

48-h LC50 = 14 mg/L

Water fleas (*Daphnia magna*) were exposed to 4-tert-butylcyclohexyl acetate at nominal concentrations of 2.8 to 28.4 mg/L (measured concentrations, 2.4 to 28.4 mg/L) under static conditions for 48 hours.

48-h EC50 = 23.4 mg/L

C(E)L50 (mg/l) = 14

Use according to good working practices to avoid pollution into the environment.

12.2. Persistence and degradability

Related to contained substances:

Fatty alcohol ethoxylate:

Disposal considerations:

> = 90% the bismuth active substance (OECD guideline 303A)

60% > CO₂ formation of theoretical value (28 d) (OECD 301B; ISO 9439; 92/69/EEC, c. 4-C)

Readily biodegradable (according to OECD criteria).

Sodium Lauryl Ether sulfate:

Easily biodegradable

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

The substance / mixture NOT contains substances PBT/vPvB according to Regulation (EC) No 1907/2006, Annex XIII

12.6. Other adverse effects

No adverse effects

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Do not reuse empty containers. Dispose of them in accordance with the regulations in force. Any remaining product should be disposed of according to applicable regulations by addressing to authorized companies.

Recover if possible. Operate according to local or national regulations

SECTION 14. Transport information

14.1. UN number

Not included in the scope of application regulations concerning the transport of dangerous goods: by road (ADR); by rail (RID); by air (ICAO / IATA); by sea (IMDG).

14.2. UN proper shipping name

None

14.3. Transport hazard class(es)

None

14.4. Packing group

None

14.5. Environmental hazards

None

14.6. Special precautions for user

No data available.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

It is not intended to carry bulk

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

No data available.

15.2. Chemical safety assessment

The supplier has made an assessment of chemical safety

SECTION 16. Other information

16.1. Other information

Description of the hazard statements exposed to point 3

H225 = Highly flammable liquid and vapour.

H319 = Causes serious eye irritation.

H336 = May cause drowsiness or dizziness.

H302 = Harmful if swallowed.

H318 = Causes serious eye damage.

H315 = Causes skin irritation.

H412 = Harmful to aquatic life with long lasting effects.

H317 = May cause an allergic skin reaction.

H411 = Toxic to aquatic life with long lasting effects.

Classification based on data of all mixture components

Main normative references:

Directive 1999/45/EC

Directive 2001/60/EC

Regulation 1272/2008/EC

Regulation 2010/453/EC

** The information contained herein is based on our knowledge at the date above.

Related solely to the product and do not constitute a guarantee of a particular quality.

It is the duty of the user to ensure that these are appropriate and complete information regarding the specific use intended.

This data sheet cancels and replaces any previous edition.
